


The Prolink logo features the word "PROLINK" in a bold, white, sans-serif font. A white, curved line arches over the letters "O" and "L", and another white, curved line arches under the letters "I" and "N".

PROLINK

A close-up, low-angle photograph of a network switch or patch panel. The device is a tan-colored metal rack-mountable unit. It features multiple rows of blue RJ45 ports and fiber optic ports. Several yellow fiber optic cables are plugged into the ports. A white label on the front of the unit reads "FIO 12 CUP". The lighting is dramatic, with a bright yellow light source creating a strong lens flare effect across the center of the image.






We provide our customers with exceptional PRODUCTS in accordance with the highest international standards and also provide SERVICES that meets our customers' needs or exceeds their expectations.

Powered by: The Prolink logo, consisting of the word "PROLINK" in a bold, white, sans-serif font, with a white, curved line arching over the "O" and "L", and another white, curved line arching under the "I" and "N".

Discription




ProLink F/O JUMPER CORD ,LC -LC-MM DUPLEX - OM3 50M

Features

-  Small Size, High Precision.
-  Zirconia 1.25mm ceramics ferrule.
-  Low insertion Loss.
-  High Return Loss.
-  Duplex Is Available.



Applications

-  Telecom and Datacom Equipment.
-  LAN/WAN
-  Device Terminals

Speciations

Connectors type	LC-LC
Cable	OM3 Duplex 50M
Fiber Type	OM3 50/125
Cable Color	Aqua
insertion loss	≤0.25 dB
return loss	≥30dB
joint endurance	>1000Times
Operating Temperature	-40°C~+70°C
Storage Temperature	-25°C~+60°C
ROHS	Meet 2002/95/EC Requirement