


The Prolink logo features the word "PROLINK" in a bold, white, sans-serif font. A white, curved line arches over the letters "O" and "L", and another white, curved line arches under the letters "I" and "N".

PROLINK

A close-up, low-angle shot of a network switch or patch panel. The device is a light-colored metal rack-mountable unit. Numerous blue RJ45 ports are visible, with several yellow fiber optic cables plugged into them. The cables are illuminated from below, creating a bright, glowing effect. The background is dark, making the device and cables stand out.






We provide our customers with exceptional PRODUCTS in accordance with the highest international standards and also provide SERVICES that meets our customers' needs or exceeds their expectations.


Powered by: The Prolink logo, consisting of the word "PROLINK" in a bold, white, sans-serif font, with a white, curved line arching over the "O" and "L", and another white, curved line arching under the "I" and "N".

Discription




ProLink F/O JUMPER CORD ,SC -SC-SM DUPLEX -20M

Features

-  Small Size, High Precision.
-  Zirconia 1.25mm ceramics ferrule.
-  Low insertion Loss.
-  High Return Loss.
-  Duplex are Available.



Applications

-  Telecom and Datacom Equipment.
-  LAN/WAN
-  Device Terminals

Speciations

Connectors type	LC-LC
Cable	SM Duplex 3.0 LSZH 20M
Fiber Type	SM 9/125
Cable Color	Yellow
insertion loss	-0.3 dB
return loss	≥45dB
joint endurance	> 1000Times
Operating Temperature	-40°C~+70°C
Storage Temperature	-25°C~+60°C
ROHS	Meet 2002/95/EC Requirement